## DT05 Rec'd PCT/PT0 0 7 OCT 2004.



## INTERNATIONAL APPLICATION TRANSLATION CERTIFICATE

•											•	
	I, th	ne be	elow	named	l ve	rifier	, her	eby c	ertify	, that	::	_
below;	(1)	My r	name	and p	ost	offic	e add	ress	are as	; stat	:ed	
the langu Applicati	lage :	in wh	nich	the b	elov	v iden	the E	nglis d Int	h lanç ernati	juage Lonal	and i	n
translati	(3) ion in	I be	eliev the E	e the Inglis	att h la	ached inguag	is a e of	full the	, true	e and	faith	ful
	·, ·	[ ] [ ] [ ]	17       	endme . 05.	nt u 200	nder F	CT Ar	ticle	e 34(2	)(b)	filed	
of Interr under the	nation	nal A	Appli	catio	on PC	CT/JPO	<u>3/04</u>	922,	filed	<u>17 A</u>	pril 2	<u>200</u> 3
personal informati these sta statement imprisonm United St jeopardiz thereon.	I decknowlden are attement, and attement, attes	clare ledge nd be nts w d the or b	fur e are elief vere e lik poth,	ther true are made e so unde	that e and beli with made r Se	all that leved the are ection wil	all: to be knowl: punis: 1001 lful	state true edge hable of T false	ments; and that we by find the little	made furth willfu ine on 18 of ements	on her th il fal the s may	se
	Signe	ed th	nis _	4th	day	of		Octo	ber, 2	0 04	<b>-•</b>	
Full name	e of v	verif	fier_	Is	samu	SAKAM	OTO		<del></del>		<del></del>	
Signature	of v	verif	ier_				Ka	Me	P		<del></del>	
Post Offi	.ce Ad	dres	ss_5-	123-4	101,	Nogam	<u>i 1-c</u>	home,	Taka	ırazul	ca-shi	,
Hyogo 665-0022 Japan												
							-					



## CLAIMS

## 1. An aroma device comprising

visible light emitting diodes (LEDs) as a light source, a first cover for covering said LEDs and for diffusing and transmitting light, a second cover, provided outside said first cover, for diffusing and transmitting the light through at least part or the whole of the side face thereof, and a heater for heating a material to be heated which emits aroma.

2. An aroma device in accordance with claim 1, wherein

said heater is disposed above said LEDs, and heater wires are wired from the center of the plurality of LEDs.

3. An aroma device in accordance with claim 1, wherein

a plurality of LEDs are provide, and respective lighting timings are shifted.

4. An aroma device in accordance with claim 2, wherein

said heater wires are bundled by a holding pipe.

of Practice of the Party of the

5. An aroma device in accordance with claim 4, wherein

the color of said holding pipe is made similar to the color of emitted light of said LEDs.

- 6. An aroma device in accordance with claim 1, wherein
- a heater having a positive temperature coefficient (PTC) is used as said heater.
- 7. An aroma device in accordance with claim 1, wherein

the surface maximum temperature of the heating surface for heating the material to be heated by said heater is set to  $160 - 300^{\circ}$  C.

8. An aroma device in accordance with claim 1, wherein

said second cover is supported in the vertical direction by a fixture member made of a transparent resin and provided inside said second cover.

9. An aroma device in accordance with claim 8, wherein

AT SA PAGE BY

the shape of at least the portion of said fixture member corresponding to the mounting positions of said LEDs is formed into a nearly cylindrical shape.

10. An aroma device in accordance with claim 1, comprising a container for accommodating the material to be heated, a heating plate disposed below said container, said heater for heating said heating plate, a supporting member, having an opening opposed to said heating plate, and for supporting said heating plate and said heater, said second cover for forming the side face of the outer shell, and a lid cover having an opening larger than the opening in said supporting member, wherein the upper portion of the opening circumferential portion formed around said opening in said supporting member is fitted to the inside of said opening in said lid cover, and the upper face of the outer portion is formed of at least the opening circumferential portion of said supporting member, said heating plate and said lid cover.

11. An aroma device in accordance with claim
1, comprising:

a container for accommodating the material to be heated.

a heating plate disposed below said

container,

said heater for heating said heating plate,

a supporting member for supporting said heating plate and said heater, said supporting member having an opening through which heat from said heating plate is transmitted to said container by virtue of contact or via an air layer, and being made of a material having a thermal conductivity lower than that of said heating plate,

said second cover for forming the side face of the outer shell, and

a lid cover, having an opening through which the heat from said heating plate is transmitted to said container by virtue of contact or via an air layer, said lid cover being mounted on said supporting member, and covering at least the outer circumferential portion of said supporting member and the upper portion of said second cover, being made of a material having thermal conductivity lower than that of said heating plate.

12. An aroma device in accordance with claim10, wherein

said lid cover and said supporting member are connected to each other by fastening members in the vicinities of their respective outer



circumferences.

13. An aroma device in accordance with claim10, wherein

the opening circumferential portion of said opening in said supporting member is exposed outside through the opening in said lid cover.

14. An aroma device in accordance with claim10, wherein

the level difference at the fitting portion between the circumferential portion of the opening in said supporting member and the opening in said lid cover is made nearly zero.

15. An aroma device in accordance with claim
13, wherein

said supporting member is provided with a liquid reservoir for storing liquid entered through the clearance of fitting portion of said opening circumferential portion and said lid cover.

16. An aroma device in accordance with claim 10, wherein

clearances are provided at the side face of said lid cover or between said lid cover and said

second cover in the vicinity of the contact portion of said second cover and the side face of said lid cover and are allocated for air ports.

17. An aroma device in accordance with claim 16, wherein

said supporting member has an upper cover and a heater cover,

said heater cover supports said heater, and said upper cover covers said heater, and

said lid cover has a wall for partitioning the space between said air ports and the contact faces of said upper cover and said heater cover, said wall being formed to a position lower than the contact faces of said upper cover and said heater cover.